

## **SCFM203**



32.63" x 76" x 28.25" (H x W x D)

Commercially listed 19.8 cu.ft. manual defrost chest freezer in white with stainless steel corner guards and lock

## **Highlights:**

Commercially approved for use in foodservice establishments

19.8 cu.ft. interior for large capacity storage

Manual defrost operation and static cooling system

## **Product Features:**

Large capacity	19.8 cu.ft. of interior storage	
Commercially approved	ETL-S listed to ANSI-NSF Standard 7 for commercial use	
Factory installed lock	Keyed lock for a secure interior (2 keys included)	
Manual defrost operation	Static cooling system with a rear-mounted drain for easier defrosting as needed	
Counterbalanced hinges	The lid will remain open once lifted for safer loading	
Thick insulation	3 1/2" thick walls ensure proper insulation for reliable storage	
Stainless steel front corner protectors	External "bumpers" included for easy installation to help protect the corners in high traffic environments	
Hammered aluminum interior	Solid construction for durable storage in busy settings	
Easy-grip handle	External handle for easy opening	





## **SCFM203 Specifications:**

Overview	
Height of Cabinet	32.63" (83 cm)
Width	76.0" (193 cm)
Depth	28.25" (72 cm)
Depth with Handle	30.0" (76 cm)
Capacity	19.8 cu.ft. (561 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Sanitation	ETL-S
Amps	3.6
Voltage/Frequency	115 V AC/60 Hz
Weight	210.0 lbs. (95 kg)
Shipping Weight	220.0 lbs. (100 kg)
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
UPC	761101080802
Freezer	
Door Swing	Lift-Up
Interior Height	24.25" (62 cm)
Interior Width	70.25" (178 cm)
Interior Depth	20.75" (53 cm)
Thermostat Type	Dial
Refrigerant Type	R290a
Refrigerant Amount	3.03 oz.
High Side PSI	400.0
Low Side PSI	200.0
Wheels	6
Compressor Step Height	10.25" (26 cm)
Compressor Step Width	11.75" (30 cm)
Compressor Step Depth	20.75" (53 cm)
Temperature Range	-10 to -26°C

