

### BI-36UG/S



# **FEATURES**

Monitor and control remotely with Wi-Fi connectivity

Preserves refrigerated foods with cool, moist air and frozen foods with frigid, dry air

Fight spoilage and odors with a NASA-inspired air purification system

Locks in cold air to ensure freshness with magnetic door seals

Keeps produce fresher with high-humidity, sealed crisper and deli drawers

Controls temperature within one degree of setpoint

Filters ice, removing contaminants, chlorine taste, and odor

Yields ice automatically and "max ice" for additional production

Display food via a single, triple-pane and UV-resistant glass door

Ensures excellent visibility with bright lights

Refer to freshness cards for tips on food preservation, use, and care

#### **ACCESSORIES**

36" Stainless Steel Kickplate

90° Door Stop

Air Purification Cartridge

**Dual Installation Kit** 

Egg Container

Stainless Steel Pro Louvered Grille - 83"

Stainless Steel Pro Louvered Grille - 88"

Stainless Steel Side Panel

Water Filter

Water Filter By-Pass Plug

White Side Panel

Dual Installation Kit with Dual Wide Grille

Stainless Steel Pro Handles

Accessories are available through an authorized dealer. For local dealer information, visit <a href="mailto:subzero-wolf.com/locator">subzero-wolf.com/locator</a>.



### **HANDLE OPTIONS**



# PRODUCT DETAILS

## REFRIGERATOR

- · 1 adjustable dairy compartment
- · 1 deli drawer with adjustable dividers
- · 1 high-humidity crisper drawer with adjustable dividers
- 4 glass refrigerator shelves (3 adjustable; 1 stationary)
- LED refrigerator and freezer lights

#### **FREEZER**

- · Automatic ice maker with removable ice container
- 1 full-extension roll-out freezer drawer





## **PRODUCT SPECIFICATIONS**

Model	BI-36UG/S
Dimensions	36"W x 84"H x 24"D
Door Clearance	37 1/4"
Drawer Clearance	23 5/8"
Weight	515 lbs
Refrigerator Capacity	16.3 cu. ft.
Freezer Capacity	5.3 cu. ft.
Electrical Supply	115 VAC, 60 Hz
Electrical Service	15 amp dedicated circuit
Plumbing Supply	1/4" OD copper, braided stainless steel or PEX tubing
Plumbing Pressure	35–120 psi
Receptacle	3-prong grounding-type

# **ELECTRICAL**


# **PLUMBING**






NOTE: Dimensions in parenthesis are in millimeters unless otherwise specified

## **INTERIOR VIEW**




This illustration is intended for interior reference only and may not represent the exterior of the model being specified.

## **DIMENSIONS**



# STANDARD INSTALLATION



NOTE:  $3^1/2^n$  (89) finished returns will be visible and should be finished to match cabinetry Shaded line represents profile of unit.