## 24" Wine Captain® Model • 1000 Series







STAINLESS FRAME

### **FEATURES & BENEFITS**

ш	
O	
Z	
4	
Σ	
~	
0	
Ĭ.	
~	
ш	
	ERFORMANCE

- Volume of 5.2 cu ft holds up to 48 wine bottles (750 ml)
- Mechanical Dial Control is conveniently located on the grille
- Approximate temperature range: 40°F 60°F
- Passive cooling system
- Rubber mounted compressor virtually eliminates vibration
- Exceeds 2019 energy standard by 34% (Tested according to 2019 Department of Energy - standard 10 C.F.R. section 430.23)

# INTERIOR/EXTERIOR

- White interior is illuminated with recessed incandescent lighting that automatically turns off when the door is closed
- Three-quarter extension zinc coated wine racks allow for easy access
- Wine racks accommodate a variety of bottle shapes and sizes, while the fourth and fifth racks allow for larger diameter wine and champagne bottles
- LowE coated, argon gas filled, dual thermopane glass door provides protection from harmful UV light
- Stainless steel handle (7/8" diameter)
- Door swing is field reversible, and is shipped right-hand hinged

## INTEGRATION

- Unit is designed to be built-in or can be freestanding with the freestanding accessory kit
- Solid natural beech wood fronts on wine racks can easily be stained to match surrounding cabinetry
- Four independently adjustable leveling legs provide a precise undercounter fit


### **MODEL DETAILS**

Model	Voltage/Hz	Door Swing	Finish	Shipping Weight
U-1024WCS-00B	115 / 60	Field Reversible	Stainless Frame	135 lb


### **ACCESSORIES**

Model	Description	Finish	Shipping Weight
ULAFREESTANDB	Freestanding Kit	Black	3 lb

### **DIMENSIONS**



### **CABINET CUT-OUT**



### **INSTALLATION NOTES**

When installing adjacent to wall, ensure 2  $\frac{1}{2}$ " clearance on hinged side for 90° door opening, allowing ample room for door handle.

Cutout includes the additional  $\frac{1}{4}$ " width overall to ensure proper installation.

No additional clearance around sides, top or rear of unit is needed for ventilation.

Do not obstruct front grille air flow.

### **SPECIFICATIONS**

Model	1024WC
Amps: Running	2.4
Capacity: Volume (cu ft)	5.2
Capacity: Wine Bottle (750 ml)	48
Control Type	Mechanical Dial
Dimensions: Product Depth	23 <sup>1</sup> / <sub>4</sub> " / 591 mm
Dimensions: Product Height	34 ½" / 867 mm
Dimensions: Product Width	24" / 610 mm
Energy Consumption: Avg. Per Year	130 kWh
ENERGY STAR	N/A
Product Weight: Max	123 lb
Refrigerant Type	R134a
Sabbath (Star K Certified)	No
Temperature Range	40°F - 60°F

### **COOLING SYSTEM**



### **ELECTRICAL REQUIREMENTS**

This unit requires a grounded, polarized 115 VAC, 60 Hz, 15 A power supply (normal household current).





Please visit u-line.com to view this model's User Guide & Service Manual. All Specifications are subject to change without notice.