

FS30LPRO



24.63" x 18.5" x 17.75" (H x W x D)

Compact manual defrost all-freezer with lock and probe hole

Highlights:

Compact size is ideal for countertop use

Factory installed access port allows users to install their own monitoring equipment

-20°C capable with manual defrost operation

Product Features:

Compact dimensions	Sized for easy use on top of counters
Factory installed lock	Keyed lock for a secure interior
Manual defrost	Static cooling system for improved temperature stability
-20°C capable	Low temperature capability ideal for certain sensitive items
Access port	Includes a factory installed probe hole for users to install their own monitoring equipment
Removable shelves	Wire shelves can be removed to accommodate different sizes or for easy cleanup
One piece interior liner	Easy clean-up with a seamless liner that won't hold a mess in hidden crevices
Flat door liner	Interior design conforms to CDC guidelines to ensure stable conditions for sensitive materials
Adjustable thermostat	Dial thermostat located inside the unit

FS30LPRO Specifications:

Overview	
Height of Cabinet	24.5" (62 cm)
Height to Hinge Cap	24.63" (63 cm)
Width	18.5" (47 cm)
Depth	17.75" (45 cm)
Depth with door at 90°	34.5" (88 cm)
Capacity	1.8 cu.ft. (51 L)
Defrost Type	Manual
Door	White
Cabinet	White
US Electrical Safety	ETL
Canadian Electrical Safety	ETL-C
Amps	0.8
Voltage/Frequency	115 V AC/60 Hz
Weight	50.0 lbs. (23 kg)
Shipping Weight	53.0 lbs. (24 kg)
Estimated Time to Ship	3 to 5 days
Parts & Labor Warranty	1 Year
Compressor Warranty	5 Years
Freezer	
Door Swing	RHD
Reversible	Yes
Interior Height	18.63" (47 cm)
Interior Width	13.38" (34 cm)
Interior Depth	13.0" (33 cm)
Shelf Type	Wire
Shelf Qty	2
Thermostat Type	Dial
Refrigerant Type	R600a
Refrigerant Amount	0.8 oz.
Level Legs	2
Compressor Step Height	8.0" (20 cm)
Compressor Step Width	13.38" (34 cm)
Compressor Step Depth	5.75" (15 cm)

