











FULGOR

MILANO

100 Series 30" Single Wall Oven

F1SM30S1



| | | |
|--|--|---|
| Series | 100 | |
| Type | NORMAL | |
| Size | 30"x24" | |
| Colour | SS | |
| Oven Type | Multifunction (True Euro Convection) | |
| Temperature Regulation | Thermostat | |
| Functions | | |
| True European Convection Bake |  | |
| Convection Broil |  | • |
| Bake |  | • |
| Broil |  | • |
| Lower Bake |  | • |
| Thaw (Defrost) |  | • |
| Maxi Broil |  | |
| Pizza (Lower Convection) |  | • |
| Convection Bake (without ring element) |  | • |
| Oven Lights |  | • |
| Control Panel | | |
| Control type | Time Programmer | |
| Clock/Timer Display | Red Led | |
| Commands | 2 Knobs / 6 Buttons | |
| Language | English | |
| Special Features | | |
| Manual Fast Preheat | | |
| Child Door Lock | | |
| Sabbath mode | | |
| 12/24 hour clock format | | |
| °C/°F | | |
| Oven Door(s) | | |
| Oven Glass Window | Large See Through Glass | |
| Door Cooling System | 3 Pane Heat Resistant Glass | |
| Door Hinges | Heavy Duty Steady Tilt | |
| Handle Style | Tubular Steel | |
| Oven Cavity | | |
| Gross Capacity (cuft) | 3.0 | |
| Usable Capacity (cuft) | 2.8 | |
| Cavity Enamel Colour | Black | |
| Rack Positions | 4 | |
| Oven Lights | 2x20W Halogen | |
| Broil Upper Heating Element | 3100 W (240V) | |
| Upper Auxiliary Element Wattage | 1032W (240V) | |
| Concealed Bake Lower Heating Element | 2100 W (240V) | |
| Lower Auxiliary Element Wattage | | |

FULGOR

MILANO

Convection Element Wattage

Accessories

| | |
|--|----------------|
| Chromed racks | 2 |
| Enameled Grill set (basin + anti splash) | 1 (only basin) |
| Telescopic chromed rack | |

Dimensions

| | |
|-----------------------|------------------|
| Overall dim - width | 29 3/8" (745mm) |
| Overall dim - height | 23 3/16" (589mm) |
| Overall dim - depth | 22 1/16" (560mm) |
| Cutout - width | 28" (710mm) |
| Cutout - height (min) | 23" (585mm) |
| Cutout - depth (min) | 24" (610mm) |

Power / Ratings (208/240 V, 60 Hz)

| | |
|------------------------------|-----------------|
| KW/Amps rating at 240V, 60Hz | 3.625kW - 15.6A |
| KW/Amps rating at 208V, 60Hz | 2.755kW - 13.7A |
| Cable + Conduit | • |

INSTRUCTIONS FOR USE

| | |
|---------------------|------------|
| Use & Care Manual | EN, SP, FR |
| Installation Manual | EN, SP, FR |