

SPECIFICATIONS

★ENERGY STAR® models

Model	UPC	Cooling Btu	Heating Btu	Volts Rated	Cooling Amps	Cooling Watts	EER	CEER	Estimated Yearly Energy Cost	Moisture Removal- Pints/HR	Refrigerant	CFM	Wt. Net/Ship Lbs.
FIXED CHASSIS, COOL ONLY (WINDOW INSTALLATION ONLY)													
★ CCF05A10A		5200	—	115	4.3	459	12.1	12.1	\$41	1.0	R410A	141	44/51
★ CCF06A10A		6000	—	115	4.3	492	12.1	12.1	\$45	0.9	R410A	141	44/51
★ CCF08A10A		8000	—	115	5.8	661	12.1	12.0	\$60	1.0	R410A	206	51/57
★ CCF10A10A		10000	—	115	7.3	826	12.1	12.0	\$75	1.2	R410A	282	64/73
★ CCF12A10A		12000	—	115	8.6	992	12.1	12.0	\$90	1.5	R410A	270	73/82
SLIDE OUT CHASSIS, COOL ONLY													
★ CCW06B10A		6000	—	115	4.3	492	12.2	12.1	\$44	0.9	R410A	200	44/51
★ CCW08B10A		8000	—	115	5.8	661	12.1	12.0	\$60	1.0	R410A	250	44/61
★ CCW10B10A		10000	—	115	7.3	826	12.1	12.0	\$74	1.2	R410A	300	51/68
★ CCW12B10A		12000	—	115	8.6	992	12.1	12.0	\$89	1.5	R410A	330	64/86
★ CCW15B10A		15000	—	115	11.0	1270	11.9	11.8	\$117	2.0	R410A	400	73/93
★ CCW18B30A		18000	—	230	7.1	1525	11.9	11.8	\$138	2.7	R410A	520	106/136
★ CCW24B30A		24000	—	230	10.2	2308	10.4	10.3	\$209	2.7	R410A	590	117/144
SLIDE OUT CHASSIS, HEAT & COOL													
CEW08B11A		8000	4200	115	6.3	670	11.0	10.9	\$61	2.1	R410A	250	44/61
CEW12B33A		12000	10600	230	4.8	1060	11.0	10.9	\$96	3.3	R410A	265	64/86
CEW18B33A		18000	10600	230	7.2	1600	10.8	10.7	\$144	5.5	R410A	430	106/136
CEW24B33A		24000	10600	230	10.6	2340	9.5	9.4	\$211	6.5	R410A	560	117/144



INSTALLATION

Model	Window Width Inches			Minimum Extension Inches		Window Width Inches		Carton Dimensions Inches		
	Height Inches	Width Inches	Depth Inches	Minimum Extension Into Room Inches	Minimum Extension Outside Inches	Minimum*	Maximum	Height	Width	Depth
CCF05A10A, CCF06A10A,	13 3/8	18 5/8	15 5/8	—	—	26	36	14 1/2	21 1/2	17 3/4
CCF08A10A	13 3/8	18 5/8	17 5/8	—	—	26	36	14 1/2	21 1/2	18 1/2
CCF10A10A, CCF12A10A	15 1/8	19 7/8	21 3/4	—	—	26	36	17 1/2	21 7/8	23 3/4
CCW06B10A, CCW08B10A, CEW08B11A, CCW10B10A, CCW12B10A, CEW12B33A,	14 5/8	19 3/4	23 3/4	—	—	26	36	17	22	26
CCW15B10A, CCW18B30A, CEW18B33A	18	23 7/8	25 3/8	—	—	26	36	19 3/8	25 5/8	29 5/8
CCW24B30A, CEW24B33A	18 5/8	27	26 5/8	—	—	26	36	19 1/2	29 1/4	31

All Chill Premier CCF models are designed for window installation only.

* Minimum widths achieved using one side curtain assembly as opposed to both in a standard installation.

CIRCUIT RATING/BREAKER

Model	Circuit Rating Breaker or T-D Fuse	Plug Face (NEMA#)	Power Cord Length (ft.)	Wall Outlet Appearance
ALL CCF MODELS. CCW06B10A, CCW08B10A, CCW10B10A, CCW12B10A, CEW08B11A	125V-15A	5-15P	6	
CCW15B10A			5.5	
CCW18B30A, CCW24B30A			4	
CEW12B33A, CEW18B33A, CEW24B33A	250V - 20A	6-20P	6	



Friedrich Air Conditioning Co. | 10001 Reunion Place, Suite 500 | San Antonio, TX 78216 | 877.599.5665 | www.friedrich.com