Chimney BWP2 SERIES

This hood offers traditional design with modern features bringing an exciting new look to your kitchen. Available in stainless steel. Bright LED lighting enhances your cooking experience, while the 3-speed backlit soft touch control makes operation easy.

SIZE	MODEL NO.	GREASE FILTERS (replacement)	NON-DUCTED CHARCOAL FILTERS
29-1/2 in.	BWP2306SS	S99010487 (set of 2)	FILTERBWPTS (set of 2)
35-1/4 in.	BWP2366SS	S99010488 (set of 3)	FILTERBWPTS (set of 2)

HVI PERFORMANCE									
	Size	Damper	Sones		CFM				
Duct Orientation			Normal	Medium*	High	Normal	Medium*	High 0.25 in. w.g.	High 0.1 in. w.g.
Round - Vertical	6 in.	Included	1.5	5.5	13.0	100	370	555	570

FEATURES	
Max Blower Airflow	630 CFM
Finish	430 Stainless Steel #4 Brushed
Wall Mount	Yes
Telescopic Flue	Yes - Accomodates 8-ft. to 9-ft. ceilings
Convertible to non-ducted operation	Yes - Non-Duct Kit ARKBWP sold separately
Blower type	Single, Centrifugal
Cord-connected	Yes
Control type	Soft-Touch Blower low speed Blower medium speed Blower high speed Light on-off 5-Minute delay
Lighting	2 x LED Modules 5.5 W, (included)
Grease Filters	Hybrid baffle filters, dishwasher-safe with quick-release latch



120 V, 60 Hz - 3.5 AMPS

OPTIONAL ACCESSO	ORIES (sold separately)

Flue Extension for 10-ft. ceiling	FXN58SS
Non-Duct Kit	ARKBWP

MOUNTING HEIGHT


24-in. from cooktop to bottom of hood


LIMITED WARRANTY

Broan-NuTone LLC

(See installation manual for full warranty text.)

FOR INDOOR USE ONLY





HVI-2100 CERTIFIED RATINGS comply with new testing technologies and procedures prescribed by the Home Ventilating Institute, for off-the-shelf products, as they are available to consumers. Product performance is rated at 0.1 and 0.25 in. static pressure at high speed based on tests conducted in an HVI-approved state-of-the-art test laboratory. Sones are a measure of humanly-perceived loudness, based on laboratory measurements. * Where noted performance rating is not HVI certified but was established in accordance with HVI Standardized test procedure.

Min. 25-3/8 Max. 40-3/8

9-11/16

19-11/16

SPECIFICATION SHEET



29-1/2, 35-1/4

Dimensions shown in inches.