

36-INCH DUAL-FUEL RANGE

DOP36P86D | TRANSITIONAL STYLE



AVAILABLE MODELS

DOP36P86DLS

Transitional 36" Dual-Fuel Range - Silver Stainless Steel Natural Gas/Liquid Propane

FEATURES & BENEFITS

- → Exclusive Four-Part Dual Pure Convection heat, air, baffle, and filter to precisely distribute heat for superior cooking results.
- Steam Assist and Convection Oven the power of steam and convection cooking in one.
- → Large oven capacity 6.3 cu. ft.
- 6 brass sealed burners.
- Powerful 22K BTU and true simmer burners.
- → Illumina™ Knobs and Ambient Light.
- > PMOLED Touch Control Panel.
- → SmartThings app with integrated Wif-Fi to control and monitor remotely.
- Auto connect to hood.

ACCESSORIES (INCLUDED)	
GLIDERACK™	
	2
STANDARD RACKS TEMPERATURE PROBE	1
WOK RING	1
CONVECTION FILTER	1
	2
BRASS BURNER CAPS	YES
BLACK BURNER CAPS	YES
ACCESSORIES (OPTIONAL)	
COOKIE SHEETS (SET OF 3)	SKU - ACSM303
GENERAL PROPERTIES	
OVEN CAPACITY (CUBIC FEET)	6.3
COOKING MODES	BAKE, BROIL, ROAST, CONVECTION BAKE, CONVECTION ROAST, PRO CONVECTION, STEAM BAKE, STEAM ROAST, CONVECTION BROIL
OVEN PERFORMANCE	
BAKE ELEMENT	3,000W - 8 PASS
BROIL ELEMENT	4,400W - 10 PASS
CONVECTION FANS	2
STEAM HEATER	500W
BURNER PERFORMANCE	30077
TOTAL NUMBER OF COOKTOP BURNERS	6
	o 16,000 DOUBLE RING
CENTER FRONT (BTU) CENTER REAR (BTU)	16,000 DOUBLE RING
LEFT FRONT (BTU)	22.000 DUAL RING
LEFT REAR (BTU)	16.000 DUAL RING
RIGHT FRONT (BTU)	22.000 DUAL RING
RIGHT REAR (BTU)	16,000 DUAL RING
PERMA-FLAME™ (AUTO RE-IGNITION)	YES
CONTROL FEATURES	
PMOLED DISPLAY	YES
NUMBER OF KNOBS	8
CONTROL METHOD	KNOBS + PMOLED TOUCH SCREEN
WIFI	YES
BLUETOOTH (HOOD CONNECTION)	YES
ILLULMINA™ BURNER KNOBS	YES / WHITE
HIGHLIGHTING COLOR	WHITE
AMBIENTLIGHTING	YES (DIMMING)
CLOCK	YES
DELAY START	YES
KITCHEN TIMER	YES
TIME OF DAY (12 HR/24 HR)	YES
TEMPERATURE (F / C)	YES
CHILD LOCK	YES
SOUND ON/OFF	YES




ADDTIONAL FEATURE	S
CLEANING TYPE	SELF CLEAN, HYBRID CLEAN, GREENCLEAN
TYPE OF GRATE	CONTINUOUS CAST IRON
CAVITY	BLACK ENAMEL COATING
RACK POSITIONS	5
CONVECTION TYPE	FOUR PART DUAL PURE CONVECTION WITH FILTER
LP CONVERSION KIT	YES
ADDITIONAL MODES	
KEEP WARM	YES
PROOF (LOWER TEMP)	YES
PROOF	YES
DEHYDRATE	YES
SABBATH	YES
DRAIN	YES
DESCALE	YES
OPTIONAL MODES	
TEMPERATURE PROBE	YES
INSTANTHEAT (NO PREHEAT)	YES WITH CONVECTION ROAST /CONVECTION BAKE

TECHNICAL DETAILS	
CIRCUIT BREAKER (A)	40
VOLTS (V)	240 / 208
FREQUENCY (HZ)	60
ENERGY SOURCE	GAS AND ELECTRIC
GAS TYPE	NATURAL GAS LIQUID PROPANE
DIMENSIONS & WEIGHT	
APPLIANCE DIMENSIONS (W X H X D) (IN.)	35 7/8" X 36" X 28 3/4"
REQUIRED CUTOUT SIZE (W X D) (IN.)	36" MIN X 24"
WARRANTY	
LIMITED, PARTS AND LABOR	2 YEARS




APPLIANCE DIMENSIONS




36"	
WIDTH	35 7/8" (121.6CM)
DEPTH (BULLNOSE)	28 3/4" (73.0CM)
C (HEIGHT)	36" (91.4CM)

INSTALLATION DIMENSIONS



* Side clearance above cooking surface to any objects, i.e., wall.



36"	
А	ELECTRICAL OUTLET 7/8" (W) X 6 7/8" (H) (25.1CM X 17.5CM)
В	GAS PIPING 7 3/8" (W) X 5 3/8" (H) (18.6CM X 13.8CM)

